

HONEYWELL GRANIT XP ACCESSORIES GUIDE



Honeywell

STANDS, HOLDERS, CORDLESS BASES, AND ACCESS POINTS



HOLDER-010-U

Wall-Mount Cup

Holder Kit: Plastic bracket facilitates mounting of scanner to wall; two mounting screws included in kit.



STND-30R00-011-4

Rigid Presentation Stand

Stand: gray, 5" rigid rod, weighted base, Granit cradle.



STND-33F00-012-4

Flexible Presentation Stand

Stand: gray, 9" flexible rod, weighted base, Granit cradle.



VMHOLDER

Vehicle mount holder

Vehicle mount kit contains vehicle mount forked holder, adjustable arm with ball joints, and mounting hardware



AP-05-100BT-07N

Bluetooth Access Point

Access point for Granit XP and Granit 1981i scanners. Class 1 Bluetooth, 100m, up to 3 Granit XP scanners can be connected (cables sold separately).



AP-100BT-07N

Bluetooth Access Point

Access point for Granit XP scanners. Class 1 Bluetooth, 100m, up to 3 Granit XP scanners can be connected (cables sold separately).



TOOLBAL

Take-Up Reel/Tool Balancer

Suspension reel commonly used for scanner mounting/retention on vehicles and in fixed locations.

CHARGE AND COMMUNICATION BASES, CHARGERS AND BATTERIES



BAT-SCN05

Smart Battery Pack

Battery: Lithium-ion battery for Xenon XP 1952 cordless scanners.



CCB22-100BT-03N

Granit XP Charge/Communication Base

Base: Charge and communication. Class 1 Bluetooth. 100m (300'), up to 3 scanners can be connected. Compatible with RS232/USB/KBW cables (sold separately).



COB22

Granit XP Charge Only Base

Base: Charge only. Only one scanner can be connected at a time. Power supply required and must be purchased separately.



MB4-BAT-SCN01NADO

4-Bay Battery Charger - Desk Mount

4-bay battery charger (NA) for use with Granit and Xenon Lithium-ion batteries, NA desktop power supply (PS-050-4000D-NA), two mounting screws (100006897), and instructions (MBC-INST).



MB4-BAT-SCN01NAWO

4-Bay Battery Charger - Wall Mount

4-bay battery charger (NA) for use with Granit and Xenon lithium-ion batteries, NA wall-mount power supply (PS-050-4000W-NA), two mounting screws (100006897), and instructions (MBC-INST).

HEATERS



520L-12-S3

Scanner Heater with Cable Retractor

12V heater for Granit scanners in freezer environments



520L-24-S3

Scanner Heater with Cable Retractor

24V heater for Granit scanners in freezer environments



520L-3648-S3

Scanner Heater with Cable Retractor

36-48V heater for Granit scanners in freezer environments



521L-12-S3

Scanner Heater

12V heater for Granit scanners in freezer environments



521L-3648-S3

Scanner Heater

36-48V heater for Granit scanners in freezer environments

CABLES AND POWER SUPPLIES

<p>CBL-020-300-C00</p> <p>RS-232 Power Cable</p> <p>Cable: RS-232(5V signals), black, DB9 Female, 3m (9.8 ft), coiled, 5V external power with option for host power on pin 9.</p>	<p>CBL-020-300-C00-01</p> <p>RS-232 Power Cable</p> <p>Cable, Industrial (for freezer temps): RS-232 (5V signals), black, DB9 Female, 3m (9.8 ft), coiled, 5V external power with option for host power on pin 9.</p>	<p>CBL-020-300-C00-02</p> <p>RS-232 Power Cable</p> <p>Cable, Industrial (for freezer temps): RS-232 (5V signals), black, DB9 Female, 3m (9.8 ft), coiled, 5V external power with option for host power on pin 9.</p>	<p>CBL-020-500-C00</p> <p>RS-232 Power Cable</p> <p>Cable: RS-232(+5V signals), black, DB9 female, 5 m (16 ft), coiled, external power with option for host power on pin 9.</p>	<p>CBL-1020-300-C00</p> <p>RS-232 Power Cable</p> <p>Cable: RS-232 (+/-12V signals), black, DB9 Female, 3m (9.8'), coiled, 5V external power with option for host power on pin 9.</p>
<p>CBL-220-300-C00</p> <p>RS-232 Power Cable</p> <p>Cable: RS-232 (5V signals), black, DB9 Male, 3m (9.8'), coiled, external power with option for host power on pin 9.</p>	<p>CBL-320-300-C00</p> <p>RS-232 Power Cable</p> <p>Cable: RS-232 (+/- 12V signals), black, DB9 Male, 3m (9.8'), coiled, external power with option for host power on pin 9.</p>	<p>CBL-500-300-C00</p> <p>USB Power Cable</p> <p>Cable: USB, black, Type A, 3m (9.8'), coiled, 5V host power.</p>	<p>CBL-500-300-S00</p> <p>USB Power Cable</p> <p>Cable: USB, black, Type A, 3m (9.8'), straight, 5V host power.</p>	<p>CBL-500-300-S00-01</p> <p>USB Power Cable</p> <p>Cable, Industrial (for freezer environments) USB, black, Type A, 3m (9.8'), straight, 5V host power.</p>
<p>CBL-500-500-C00</p> <p>USB Power Cable</p> <p>Cable: USB, black, Type A, 5m (16.4'), coiled, 5V host power.</p>	<p>CBL-501-300-S00</p> <p>USB Power Cable</p> <p>Cable: USB Granit scanner cable, compatible with USB D9 connectors on VM series docks.</p>	<p>CBL-503-300-C00</p> <p>USB Power Cable</p> <p>Cable: USB, black, 12V locking, 3m (9.8'), coiled, 5V host power.</p>	<p>CBL-503-300-S00</p> <p>USB Power Cable</p> <p>Cable: USB, black, 12V locking, 3m (9.8'), straight, 5V host power.</p>	<p>CBL-503-500-C00</p> <p>USB Power Cable</p> <p>Cable, USB, black, 12V locking, 5m (16.4'), coiled, 5V host power.</p>
<p>CBL-720-300-C00</p> <p>KBW Power Cable</p> <p>Cable: KBS, black, PS2, 3m (9.8'), coiled, 5V external power with options for host power.</p>	<p>CBL-720-370-C00</p> <p>PS-2 Power Cable</p> <p>Cable: PS-2 Keyboard Wedge, Coiled, 5V.</p>	<p>MX009-3MA8SN</p> <p>USB Power Cable</p> <p>Cable: USB POS, Type A, Straight, Black, No PowerL</p>	<p>46-00525-6</p> <p>Power Supply – NAPlug</p> <p>Power Supply: NA plug, 1.0A@ 5.2VDC, 90-255V AC @ 50-60 Hz.</p>	<p>46-00526</p> <p>Power Supply – EUPlug</p> <p>Power Supply: EU plug, 1.0A@ 5.2VDC, 90-255V AC @ 50-60 Hz.</p>
<p>46-00528</p> <p>Power Supply – AUPlug</p> <p>Power Supply: AU plug, 1.0A@ 5.2VDC, 90-255V AC @ 50-60 Hz.</p>	<p>46-00529</p> <p>Power Supply – CNPlug</p> <p>Power Supply: CN plug, 1.0A@ 5.2VDC, 90-255V AC @ 50-60 Hz.</p>			

Honeywell Safety and Productivity Solutions

9680 Old Bailes Road
Fort Mill, SC 29707
800-582-4263
www.honeywell.com

THE
FUTURE
IS
WHAT
WE
MAKE IT

Honeywell